

Product specification

Customer
Danske Bank A/S
DK-3460 Bikrerød

Auftragsnummer / Auftragsdatum
1249136 / 16.05.2014
Sachbearbeiter
Mr. Hermann Huevet
Tel: +49(0)5951/209-286
Fax: +49(0)5951/209-98286
hermann.huevet@krone.de

Date: 06.07.2023
Page 1 of 8

Equipment: F0624770
Equipment: F0624770
Equipment: F0624770

T 000.046 s-registration (Sweden)
T 000.100 Without country symbol sticker
T 001.328 Lettering on name plate: Typ: SD, certificate no.
 e1*2007/46*0232
T 001.100 Max registered king pin load: 12.000 kg
T 001.200 Max registered Axle load: 24.000 kg
T 001.300 Allowable gross vehicle weight: 36.000 kg
T 001.040 Max technical tow bar load: 12.000 kg
T 001.051 Max practical axle load: 27.000 kg Gross vehicle weight:
 39.000 kg
T 500.003 Suitable for towing vehicle according to ISO 1726: (ISO
 1726 limited - towing vehicle unit data required)
T 500.005 Distance from Kingpin to centre of support device: 2.267 mm
T 002.300 5th wheel height unloaded: 960 mm
T 002.405 # [TO TRANSLATE!!!]

Chassis

A 100.012 Double T-longitudinal beams and cross members including
 side rave with cross members and extensions all fully
 welded construction
A 100.103 Award winning Multilock side rave including load securing
 positions every 100 mm
A 100.300 Neck height: 80 mm (incl. floor and rubbing plate)
A 100.014 2" King pin (corner dimension: 2.040 mm)
A 110.002 Rear bumper, round bar (for RoRo), according to EC regulation
A 100.072 Side guard
A 300.600 For load area length: 13.620 mm

A 491.000	For load area width: 2.480 mm
A 033.110	7 pairs of post pockets 81 x 81 mm in side rive and 7 post pockets 81 x 81 mm centrally located (not in neck area) in the floor
A 420.135	Note: Post pockets / plug in posts not designed for the sole cargo securing
A 042.000	4 pairs of ferry shackles according to PREN 29367-2
A 001.000	Pull out ladder at rear
A 001.020	Door catch

Supporting legs

B 028.014	2 mechanically operated landing legs, 2 x 12 tons capacity, with base plate, Brand: Krone-choice
B 001.000	Landing legs operated from right side
B 028.011	Reinforcement of landing legs strut at the rear: approx. 45 degrees Attention: restricted clearance for later installation of a pallet box!

Axles/Suspension

C 000.004	3 axles each with a load capacity of 9.000 kg
C 143.024	Distance from kingpin to centre of axle unit = 7.630 mm
C 100.010	Wheel base: 1.310 / 1.310 mm
C 038.000	Rims centrally aligned
C 020.010	VALX axles with air suspension, drum brakes (360x200 mm)
C 080.260	air suspension with total travel 260 mm
C 043.000	Including raise and lower valve, 1 valve
C 145.040	Levelling valve mounted on the central axle
C 145.050	Attention: raise and lower valve approx 300 mm further back

Tyres (rims)

D 410.061	6 x 435/50 R 19.5, brand: Krone choice (from a European, Chinese or Japanese production)
D 185.100	Without spare wheel
D 300.000	Rims centred

Spare wheel carrier

E 070.000	Without spare wheel holder
-----------	----------------------------

Mud guards

F 002.010	Wheel covering according to EC-regulations
F 010.001	Spray suppression according to EC guideline

F 002.126 mud flap with "DSV" - Logo

Brakes

G 000.103 Brake system according to EC-re. 71/320//EWG ff or ECE R 13
G 082.000 Spring parking brake
G 079.001 Brake air pipes, approx. 800 mm above platform level
G 102.010 Diagnostics by ISO7638 plug connection (EBS supply cable)
G 039.011 without wheel chocks and without holder
G 072.020 Additional coupling head (supply line) for second drive level
G 088.540 Braking system, brand: Wabco / Type: EBS-E
G 066.211 "Lommy-GRP-Unit" mounted to the subpanel; Equipment to be supplied free issue by customer
G 088.200 EBS-Modulator with RSS (Roll Stability Support)
G 088.500 Attention: The trailer is only allowed on towing vehicles with compatible braking systems!
G 085.100 EBS-braking system, 2S/2M, 2 sensors on 1 axle

Light

H 000.001 Lights according to UN ECE Regulation No. 48
H 045.027 2 number plate lights (LED)
H 070.005 2 LED outline marking lights with rubber-arm
H 071.010 LED Side marker lights
H 007.002 Electric-cable connection at front , approximately 300 mm above platform
H 001.000 24 volt, at front, with 7-channel power socket DIN ISO 1185
H 080.000 7-channel-power socket DIN ISO 3731 at front, for add.uses
H 013.001 Two 3-chamber rear lights, round
H 031.000 1 fog light
H 021.000 1 reverse headlight
H 021.011 1 additional reverse headlight

Accessories

I 130.013 Delta steel buffers across rear frame
I 013.110 PVC document tube (110 mm), mounted behind landing legs, right side
I 130.018 Trapezium shaped steel buffers at outer rear + delta profile
I 010.017 2 warning plates ECE R 70 (red/yellow), on rear doors, in plastic foils, horizontal
I 017.000 1 Orange warning plate(s), foldable (without number)

- I 010.010 Installation instructions orange Warning Plate: left side, 15 cm directly above the yellow / red warning sign, right justified
- I 062.207 17 Lashing straps and ratchet (2 parts), with round pipe fitted to the side frame, lashing capacity 2500 dnA, left hand side; ratchet on 500mm strap tied up to the first row of planks; right hand side; 10000 mm strap tied up to the 2nd row of planks.
- I 011.110 Attaching 'service and info' stickers: * Tightening wheel nuts, check wheel pressure etc. * Additional attaching of 2 ferry stickers on the front wall left and right side near the centre sill
- I 011.029 Advice: License plate with screw and nut!

Floor

- W 000.028 Floor type: BO 13620
- W 048.110 30 mm thick, phenolic coated plywood floor, sectioned area fully waterproofed and sectional areas sealed. Resistance according to DIN 283; for floor loadings up to 7.000 kg forklift axle load.
- W 048.105 Premium floor sealing

Roof frame

- M 000.125 Type: AB 13620 AGG, internal length 13.620 mm, internal width acc. to stanchions
- M 483.000 Aluminium cant rail, continuous, for support of sliding curtain and sliding posts
- M 695.114 EDSCHA sliding roof (175) with plastic joints, height 175 mm, gradient 0 mm, suitable for transport of mesh containers according to DIN 15155
- M 550.000 Side access height, floor to cant rail at front: 2.860 mm
- M 550.005 Side access height, floor to cant rail at rear: 2.860 mm
- M 550.570 Internal height with closed roof: 3.000 mm
- M 551.000 Rear access height (through rear frame): 2.845 mm
- M 550.411 Total height (unloaded) approx. 4075 mm
- M 743.110 Lifting roof, hydraulic, liftable up to 500 mm at 4 corner posts separately
- M 743.121 Adjustable driving height, front, lowering device from basic position 150 mm (in 50 mm steps), reduced lift: 350 mm
- M 743.122 Adjustable driving height, rear, lowering device from basic

	position 100 mm (in 50 mm steps), reduced lift: 400 mm
M 743.185	Note: Lifting roof lowered for pick up, front/rear 2x50 mm
M 080.005	Rubber lip seal at cant rail: grey
M 072.001	Roof also movable to rear (roof curtain fixable to front roof cover and if necessary diagonal tension has to be released before moving)
M 080.000	Diagonal roof spanning
M 044.011	4 Set(s) of wooden planks (96x25 mm)

Front wall

N 253.008	Steel front wall with bolted corner posts, side loading restricted
N 253.010	Front wall inner reinforced with plywood
N 129.020	Delta shaped profile at the Coupling bearing
N 281.002	Quick release for side curtains on front wall
N 129.001	Holder for curtain cord at front wall

Rear wall

N 303.001	Steel container rear doors including bolted steel frame, integrated door locks and concealed door hinges; roof traverse hinged and movable
N 308.015	Rear wall painted
N 224.101	Door locks with tilt locking
N 224.001	Double door locks for container rear door
N 281.010	Curtain clamping device at rear frame with ratchet
N 089.504	Fixing of tensioning pole (sliding roof) on rear wall
N 350.001	Loading width at rear doors 2.480 mm

Drop sides

N 239.000	Without drop sides
-----------	--------------------

Posts (stakes)

P 010.013	3 pairs of side posts, positioned opposite each other symmetrically, with 6 different mounting positions on each side of the chassis, Loading width between side posts 2.480 mm
P 011.011	Plank pockets for stanchions: 1 set on floor level suitable for 4 sets of planks
P 011.002	5 sets of plank pockets in stanchions

Accessories

R 086.000		Without customs seal
R 105.035		Sticker 'Load security certified' (VDI 2700 / EN 12642 XL)
R 105.030	#	4 Hazardous material sign pockets, curtain fabric (grey),
	#	310x360mm, on rear wall
	#	[TO TRANSLATE!!!]
R 105.031	#	4 hazardous material sign pockets, curtain fabric (grey),
	#	310x360mm, on front wall
	#	[TO TRANSLATE!!!]
R 105.061		without KRONE service sticker

Curtain

S 395.001		1 PVC curtain, with full lengths vertical reinforcements, top with rollers for sliding, bottom with tensioners, materialquality 850 gr./m ²
S 451.021		Anti tilt load security with brakes, made from stainless steel, lock release below
S 381.001		Curtain provided for sliding roof
S 460.001		Curtain produced accordingly to fit pre-adjusted roof height
S 100.002		Roof curtain yellow
S 100.005		Roof curtain ADR, DIN 75200 in 680 gr. design
S 089.000		TIR cord fitted
S 071.106	#	pockets for hazardous material signs on curtain, 310x360
	#	mm (4 left/4 right)
	#	[TO TRANSLATE!!!]
S 456.010		Curtain without Krone label
S 456.005		Curtain pole strap with integrated grip handle
S 100.031		White, part outline markings according to ECE-R48, on both sides of curtain
S 100.026		red, reflective outline marking on rear door, ECE-R48

TÜV-Approval

Z 010.002		Approval of the EC certificate of conformity according to Annex IX of Directive 2007/46/EC approval: e1*2007/46*0232*06
Z 030.000		CEMT-certificate, German
Z 050.005		Load security certificate according EN 12642 Code XL
Z 900.000		Attention: by pick up of trailer please note the vehicle's total height. We have special att. to the following points: 1) The common carrier is in authority for damages. 2) For

the transfer of the vehicles, we assume no liability. 3)
The carrier must seek self-About a permit under § 29 of
Road Traffic Regulations.

Painting

- X 000.021 Type: paint 13620 S
- X 001.002 Steel parts are shot blasted, KTL-primer coated and powder coated
- X 001.100 Due to different production sites slight color differences of attachments occur.
- X 049.015 DSV-Fleet numbers, (in white adhesive film), on front wall in driving direction on r.h.s. bottom on rear door in driving direction on r.h.s. inside of rear corner post in driving direction on r.h.s. (without DSV)
- X 056.005 Fleet numbers, height 100 mm, white adhesive film Placing: on front wall in driving direction on l.h.s. bottom Fleet no. = license number!

1. Color : 1

Position 10300

- X 122.000 4 sides labeling
- X 122.000 -on the sides
- X 122.000 -at the back
- X 122.000 -in front
- X 122.000 Contact person: Sören Lund
- X 122.000 Email: Soeren.Lund@DSV.COM
- X 600.001 Clearing Labeling over the customer is nessessary
- X 600.000 Designnumber: BK-DSV-M010
- X 998.147 Chassis including side rave MB 7350 NOVA GREY SDGL
- X 998.130 Axles including hub RAL 9005 JET BLACK
- X 998.890 Attachment parts BLACK OR GALVANIZED
- X 998.212 Rims SILVER NATURE
- X 998.272 Side guards WHITE POWDER COATED
- X 998.252 Rear bumper WHITE POWDER COATED
- X 998.262 Light panel WHITE POWDER COATED
- X 998.742 Side posts (Curtain sider) KTL PRIMER COATED
- X 998.537 Upper structure (front wall/rear portal/rear wall) RAL 5003 SAPPHIRE BLU
- X 998.831 Landing legs RAL 9005 JET BLACK

Danske Bank A/S
Equipment: F0624770

Date:06.07.2023
Page 8 of 8

X 998.828 Ferry shackles RAL 1004 GOLDEN YELLOW
S 998.100 Curtain colour: RAL 5003 SAPPHIRE BLUE